



Type **PNRH** - tonnage **X,X** - stroke **XXX** / serie **XX X** Linked option

Type **RNRH** - tonnage **X,X** / serie **XX**

Repair kit

Compact self contained.

		models	PNRH-0,3-	PNRH-0,5-	PNRH-0,8-	PNRH-1,5-	PNRH-3,0-	PNRH-5,0-		
(L = k + 2 x Stroke)	constant k=>		50	63	63	92	92	92		
	height=>		L	L	L	L	L	L		
	Stroke	-007								
		-010		70	83	83	112			
		-015		80	93	93	122	122	122	
		-020		90	103	103	132	132	132	
		-025		100	113	113	142	142	142	
		-032		114	127	127	156	156	156	
		-038		126	139	139	168	168	168	
		PNRH-x,x-	-050		150	163	163	192	192	192
			-063		176	189	189	218	218	218
			-080		210	223	223	252	252	252
	-100			250	263	263	292	292	292	
					313	342	342	342	342	
						412	412	412	412	
						492	492	492		
								592		
	refer.	PNRH-0,3-	PNRH-0,5-	PNRH-0,8-	PNRH-1,5-	PNRH-3,0-	PNRH-5,0-			
cil.:	Initial force in daN at 130bar	F.in.	256	400	625	1.226	2.502	4.228		
	Initial force in daN at 150 bar	F.in.	296	462	722	1.414	2.886	4.878		
	area (cm ²)	área	2,01	3,14	4,91	9,62	19,63	33,18		
	diameter of the rod	Ød	16	20	25	35	50	65		
	diameter of the body	ØD	38	45	50	75	95	120		
		L1	1			3				
		L3	4,5	6,5		8	9	10,5		
		L6	11,5	14,5		18	21	22,5		
		R		1	2		2,5			
cil. Base:	valve	Ve	bottom port G 1/8" thread							
	linked default	Ø lpd	not available							
	linked option "V"	Ø lop	not available	Bottom port 1/2" thread,"V"						
	holes	M								
	diameter drilling	ØD2								
flanges:	round flange superior	-04-	PNB-04-003	PNB-04-005	PNB-04-008	PNB-04-015	PNB-04-030	PNB-04-050		
	single flange sup./inf.	-09-	PNB-09-003	PNB-09-005	PNB-09-008	PNB-09-015	PNB-09-030	PNB-09-050		
	square flange sup./inf.	-10-	PNB-10-003	PNB-10-005	PNB-10-008	PNB-10-015	PNB-10-030	PNB-10-050		
	round external diameter	ØA	68	86	95	122	150	175		
	split external dimension	Ø A	55	70	75	100	120	140		
	diameter drilling	ØC	56,6	70,7	80	104	130	155		
	diameter of the holes	ØE	7	9		11	13			
	height	H	9	13		16	18	21		
	part inferior to the top of the stem	L11	17	24		29	33	36		

The PRODTY is holder of Brazilian and international patents, that collect characteristics of their drawings.